


TIMELESS ARTISTRY









Montano

We deliver the caliber that is essential for discovering the ideal

Coendless

BUCOLIC TURFS.

The Montano matte collection has a muddy glace that offers it a worn or vintage appearance. Due to its superior wet traction over matte polished finishes, matte tiles are a common choice for wet area applications.

A matte finish adds a touch of a classy, sophisticated appearance to your residence. The erratic surface finish of Montano tiles lends a rustic appeal to any design. it is an adept choice for modern residential designs.

www.mottogroup.in







MAKE YOUR HOMEY CLASSY WITH HUES THAT VARY

In compact spaces, a matte finish is the ideal choice. Despite compromising elegance or beauty, deploy these mosaics to make your existence smoother.


With their unique attributes, these slabs collections are flawless. Since matte patterns frequently have a natural and rustic vibes, it is important to choose a texture or pattern that complements the alcove's decor.


4 COLOURS

Since chromatic subtleties are a significant characteristic of this finish, the hue palette of matte finish tiles contains a broad variety of shades, including carbon, grey, smoke, and sand.











EASY TO CLEAN

Matte surface tiles are exempt from frequent cleaning due to the best concealing of smudges and stains.

STAIN RESISTANT

The most appealing aspect of matt finish tiles is that they require no maintenance.

SCRATCH RESISTANT

when it comes to the scratch resistance feature, it will win the top spot. A Matte surface prevents scratches.

CHEMICAL RESISTANT

Our chemical-resistant tiles provide great durability against abrasion, antiskid qualities for worker safety, and an attractive appearance.

FROST RESISTANT

Frost-resistant tiles are not damaged by extremely low temperatures. tile has the ability to endure freeze/thaw temperatures without significant harm.

CHOOSE WISELY WITH A SUPERIOR SURFACE CRUX

Rustic Matt Tiles are a great option for high-humidity spaces like the kitchen or bathroom. Rustic Matt tiles are simple to keep clean with periodic mopping. Its rough texture lends it to slippery flooring and provides a build-in anti-skid feature.

TECHNICAL FEATURES





Removable &

Reuse



Easy to

Frost Resistance



High Load Resistance

Chemical

Resistance







Ecological Finish

I

Fire Proof

APPLICATION AREAS



OFFICE TABLE



TABLE
























∽endless

Montano

FULL BODY

Endless : **04 Faces**

Type: Fullbody + Printing










Endless: **04 Faces**Type: **Fullbody + Printing**


coendless



FULL BODY










Endless : **04 Faces**Type : **Fullbody + Printing**


coendless




FULL BODY









Endless : **04 Faces**Type : **Fullbody + Printing**

coendless


FULL BODY




MANUALLY TRANSPORTING TILES


Only for 1/4" Slabs


MOVING A TILE





RAISING A IMMODERATE TILE ONTO A BENCH









✓ CORRECT

HANDLING IMMODERATE TILE FOR WALL









WORKING WITH THE VARIOUS VERSIONS OF TILES

CUTTING WITH DIAMOND DISCS





Our products can be cut using diamond discs fitted onto the hand-held electrical grinding machine. The speed of Disc rotation must be high (>10000 RPM) and should have a low feed rate (< 1 m/min). Itmay be required to cool the disc with water. Recommended discs are the thin typesgenerally used for cutting porcelain stoneware. The surface should be kept on a FLAT base while cutting without any gap underneath

DRILLING





You can use cutting discs fitted to battery-operated screwdrivers or angle grinders, electrical drills as an alternative.

INTERNAL CUT / L-SHAPED CUT



To get internal and L-shaped corners & to reduce the risk of breakage. round o the vertex of the internal corner using bits with a radius of at least 5mm. Then cut with diamond discs, be cautious to stop moving the cutting tool forward. To drill and cut using diamond discs, follow the instructions provided above.

When using these tools:

-Cool the point being drilled with water


-Don't put too much pressure and bear in mind the resistance of the type of laminated stoneware you are working on


-If you are using tungsten bits, start drilling at a low speed

-If you are using drills or screwdrivers, do not select hammering mode

EDGE-FINISHING







INSTRUCTIONS FOR MANUAL INSTALLATION

SINGLE LAYER METHOD

DOUBLE-LAYER METHOD

COMPRESSING THE TILE







IMPORTANT

All cutout corners must have a minimum diameter of 1/4". Never leave 90° angles. We recommend radiuses of more than 1/4" when the kitchen the design allows as it makes the countertop firmer.











CLEANING & MAINTENCE

Our products are non porous (due to their high quality raw materials, stringent production parameters and state of the art technology), hence any dust or deposited waste cannot penetrate the surface.

For most cases only a damp cloth is sufficient for cleaning.

Regular cleaning highlights the aesthetic features of the surface and gives it exceptional shine.

For highly aggressive cleaning caused by some common food and substances follow the table below.

TYPE OF STAIN	CHEMICAL PRODUCT	EXAMPLE	
Grease	Alkaline - Solvent	Detergent	
Oil	Solvent	Ammonia, Backing Soda	
Ink	Oxidant - Solvent	Alcohol, Liquid Bleach, Nail Paint Remover	
Rust	Acid	Hydrochloric Acid, Vinegar, Red Harpic	
Lime	Acid	Descaling Reagent, Hydro Chloric Acid	
Cement	Acid	Hydro Chloric Acid	
Wine	Alkaline	Ammonia, Liquid Bleach	
Coffee	Alkaline - Solvent	Ammonia, Liquid Bleach	
Rubber	Solvent	Alcohol, Thinner	
Plaster	Acid	Hydro Chloric Acid	
Candle Wax	Solvent	Alcohol, Thinner	
lodine	Oxidant	Liquid Bleach	
Blood	Oxidant	Liquid Bleach	
Ice Cream	Alkaline	Liquid Bleach	

Note: It is recommended that any kind of stain needs to get clean immediately / as soon as possible.

TECHNICAL SPECIFICATIONS

CHARACTERISTIC	STANDARD AS PER ISO-13006/2018 En14411 gr.bla	MOTTO VALUE	TEST METHOD
	Regulatory Prope	erties	
Deviation in Length & Width	<u>+</u> 0.5%	<u>+</u> 0.2%	ISO 10545-2
Deviation in Thickness	<u>+</u> 5%	<u>+</u> 5%	ISO 10545-2
Straightness of Sides	±0.5%	<u>+</u> 0.2%	ISO 10545-2
Rectangularity	<u>+</u> 0.5%	<u>+</u> 0.2%	ISO 10545-2
Surface Flatness	<u>+</u> 0.5%	<u>+</u> 0.3%	ISO 10545-2
Colour Difference	ΔE<1.00	∆E<0.30	ISO 10545-16
Glossiness	As per Mfg.	As Per Mfg.	GlossMeter
	Structural Proper	rties	
Water Absorption	≤0.5 %	≤O.3 %	ISO 10545-3
Apparent Density	As Per Mfg.	>2.20 g/cc	ISO 10545-3
	Massive Mechanical F	Properties	
Modulus of Repture	Min.35N/mm²	Min.40N/mm²	ISO 10545-4
Breaking Strength	Min. 1300 N	Min. 2000 N	ISO 10545-4
Impact Resistance	As per Mfg.	Min. 0.55	ISO 10545-4
	Surface Mechanical P	roperties	
Surface Abrasion Resistance	As per Mfg.	Min. class 3	ISO 10545-7
Moh's Hardness	As per Mfg.	Min. class 4	BS EN 15771
	Thermo Hygrometric F	Properties	
Frost Resistance	As Per Mfg.	Frost Proof	ISO 10545-12
Thermal Shock Resistance	Min. 10 Cycle	Min. 10 Cycle	ISO 10545-9
Moisture Expansion	Max. 0.6mm/m	Max. 0.02mm/m	ISO 10545-10
Thermal Expansion	Max. 9.0 x 10 ⁻⁶	Max. 6.0x10 ⁻⁶	ISO 10545-8
	Chemical Proper	ties	
Chemical Resistance	As Per Mfg.	No Damage	ISO 10545-13
Stain Resistance	Resistant	Resistant	ISO 10545-14
	Safety Properti	es	
Slip Resistance	As per Mfg.	N. A.	DIN 51130
Fire Resistance	As per Mfg.	Fire Proof	N. A.

PACKING DETAILS

Dimension (mm)	No. of PC's/Box	Square Feet	Weight (Approx)
800x1600mm	2 Pcs.	27.5 Sq. Feet	53 Kg.



MOTTO GROUP

8-A, National Highway, Sartanpar Road, At. Sartanpar, Ta. Wankaner, Morbi - 363 621, Gujarat, INDIA

 $\textbf{Mail.} \ in fo@mottogroup.in, \textbf{Web.} \ www.mottogroup.in$

Toll-free. 1800 123 2124 **Call.** +91 95123 80072